



LEAD-FREE PEDESTAL GEAR PUMPS FOR MAPLE SYRUP APPLICATIONS

Model OBNL3000LR

PERFORMANCE CURVE



DIMENSIONS



Features

- Lead free and corrosion resistant
- Helical gears for quiet operation
- Stainless steel shafts & fasteners
- Synthetic braided compression packing (with PTFE dispersion)
- 3/8" NPT ports

Mounting & Drive Arrangement

Pumps should be mounted on a rigid base and properly aligned with the motor. Direct drive via flexible shaft coupling is the preferred method. When a belt drive is needed, additional support is necessary to absorb the added pulley load.

Liquids & Temperature

Service life will be increased if the liquid pumped is clean and has some degree of lubricity. These positive displacement pumps have tight tolerances. When possible, flush the pump after each usage.

Temperature extremes are detrimental to service life and should be avoided. Basic metals of construction allow a temperature range of -40 to 220°F. Allowing a liquid to freeze in the pump can cause damage.


Suction Lift


Close tolerances and the positive pumping action make the rotary gear pump capable of lifting water on the suction side as high as 20 feet. Though gear pumps are self-priming, a foot valve is recommended. If possible, wet the gears with liquid to be pumped for the first dry start. Liquid retained in the system and gear chambers serves to "wet" the pump on subsequent starts. When possible flush pumps after usage.

PARTS LIST - OBNL3000LR

| ITEM NO. | DESCRIPTION | COMPONENT NO. | QTY. |
|----------|-------------------------|---------------|------|
| 1 | Packnut | OB1762-01 | 1 |
| 2 | Packing | OB5479 | 2 |
| 3 | Body | OB9318BC1N-1 | 1 |
| 4 | Grease Fitting | OB5390-01 | 3 |
| 5 | Drive Shaft & Gear Assy | OB50037 | 1 |
| 6 | Idle Shaft & Gear Assy | OB50038 | 1 |
| 7 | O-Ring | OB9797-041 | 1 |
| 8 | Cover | OB9323BN5B-1 | 1 |
| 9 | Screw | OB5385 | 8 |
| 10 | Dowel Pin | OB8885 | 2 |
| 11 | Pump Tag | OB9344 | 1 |
| 12 | Tag Screw | OB9345 | 2 |
| 13 | Lead Free Tag | OB50003 | 1 |
| 14 | Adjusting Screw | OB50025 | 1 |
| 15 | Bypass Nut | OB50026 | 1 |
| 16 | Plug Nut | OB50027 | 1 |
| 17 | Ball | OB5206 | 1 |
| 18 | Spring | OB5207 | 1 |
| 19 | Lock Nut | OB50028 | 1 |
| 20 | OB9797-021 | O-Ring | 2 |
| 21 | OB9797-018 | O-Ring | 1 |

| REPAIR KIT | | |
|----------------|-------------|--|
| Part No. | OBNL3000LRK | |
| Items Included | 2, 5, 6 & 7 | |









5900 Firestone Drive Syracuse, NY 13206 800-448-1668 oberdorfermail@gardnerdenver.com www.oberdorferpumps.com





©2018 Gardner Denver, Inc. Printed in U.S.A. OB-OBNL3000LR 1st Ed. 11/18